



Fall Protection System

With the LEOS Fall Protection System (FPS) we ensure optimal worker safety in the cleaning, repair and inspection of aircraft wings– gaining maximum effectiveness with minimal risk.



CUSTOMER ADVANTAGES

- **quick and easy set up**
- inexpensive alternative to OEM Tool
- EASA Part 21/J design approval
- complies with 89/686/EEC

The FPS is designed for up to two people, quick and easy to install and therefore particularly attractive to maintenance organizations. Besides the dynamic rope and attach-anchors the special feature of the system is the vacuum anchor, which is attached in the center between the two anchorage points on the fuselage and wingtip. This vacuum anchor is either operated by compressed air from a hangar compressed air supply or via a compressed air bottle screwed into the vacuum anchor. Protected by a multipurpose safety harness, a Block StopMini connector with integrated energy absorber, a maintenance mechanic can move along the entire surface of a wing. The Fall Protection System (FPS) has EASA Part 21/J design approval and complies with the requirements of directive 89/686/EEC and standard EN 795.

Available for:

- A320 Family
- A330
- A340

Contact

Lufthansa LEOS GmbH
Sales, Marketing & Product Development
Lufthansa-Basis
D-60546 Frankfurt/Main
Germany

Hotline: +49-69-696-8222

Fax: +49-69-696-93888

Email: sales@lufthansa-leos.com

www.lufthansa-leos.com